




RECOMMEND P.C.B LAYOUT

TOLERANCE UNSPECIFIED $\pm 0.05\text{mm}$

REV.	ECN	DESCRIPTION	MDF'D	DATE
A0	———	新订图面	Lee	2022.09.25

NOTES:

SPECIFICATION:

- 1.CURRENT RATING: 5.0 A
- 2.VOLTAGE RATING: 5.0 V
- 3.VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX
SHIELD: 50mΩ/MAX
LLCR MAX. CHANGE OF ALL PINS: 10Ωm
- 4.INSULATION RESISTANCE: 100MΩ MIN
- 5.DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1MINUTE
- 6.INSERTION FORCE: 0.5~2.0kgf
- 7.UNMATING FORCE: 0.8~2.0kgf
- 8.DURABILITY: 10000 CYCLES
- 9.OPERATING TEMPERATURE: -35°C~+85°C
- 10.THE PEAK TEMPERATURE ON THE BOARD SHALL
BE MAINTAINED FOR 10 SECONDS AT 210-250°C
- 11.WATERPROOF:IP-X7.

USB TYPE C PIN ASSIGNMENTS

PIN NUMBER	SIGNAL NAME	PIN NUMBER	SIGNAL NAME
A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

TABLE:

NO	PART	Q'TY	Material
1	PLASTIC SHELL	1	PA&LCP UL94 V-0 BLACK
2	SHELL	1	STAINLESS STEEL,NI PLATED
3	CONTACT	16	COPPER ALLOY,TIN/Au/NI PLATED
4	MD PLATE	1	STAINLESS STEEL,NO PLATING
5	MD HOUSING	1	PA&LCP UL94 V-0 BLACK
6	WATERPROOF RING	1	SILICONE UL94 V-0 BLACK



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

品名 (ITEM NO)

TYPE C 16P 立式防水母座DIP H=10.5

料号 (PART NO)

图号 (DWG NO)

页码 (SHEET)

1/1

單位(UNIT): MM

版本 (REV)

A0

比例 (SCALE) 1:1

日期 (DATE)

2022. 09. 25

设计 (DESIGN)

Lee

	未注公差
	TO GO UNLESS SPECIFIED

审核 (CHECKED)

L S V

X. X	± 0.20
X. XX	± 0.15
X. XXX	± 0.10
X°	$\pm 5^\circ$
X. X°	$\pm 2^\circ$

核准 (APPROVED)

C J I

X. AAA	± 0.10
X°	$\pm 5^\circ$
X X°	$\pm 2^\circ$

These drawings and specifications are the property of Dongguan Xibang Electronics Co., Ltd. and should not be copied. Without the prior written consent of Dongguan Xibang Electronics Co., Ltd., it shall not be copied or used in any way