

F

E

D

C

B

A




RoHS
Compliant

SYMBOL

REVISION


APPROVAL

DATE



SPECIFICATIONS

- 1.RATING:1A 30V DC
- 2.CONTACT RESISTANCE:100mΩ Max
- 3.INSULATION RESISTANCE:100MΩ Min
- 4.WINSAND VOLTAGE:500 AC FOR 1 MINUTE
- 5.OPERATING FORCE:550gf;750gf;850gf
- 6.LIFE:50000 CYCLES.



CIRCUIT

No.	DESCRIPTION	MATERIAL	QTY.	FINISHING
1	KNOB	POM	2	WHITE
2	COVER	POM	1	WHITE
3	TERMINAL①②	C2680	2	Ag PLATED OVER Ni PLATED
4	BUTTON	POM	1	WHITE
5	CONTACT PLATE	C2680	1	Ag PLATED OVER Ni PLATED
6	TERMINAL	C2680	1	Ag PLATED OVER Ni PLATED

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME

TORCH SWITCH

DRAWING

L.Liu

DWG.No.

P91

PART NO.

XB-TPS-11D17-N-850

CHECK

G.C.Chen

REV.

B

UNIT:
mmTOLERANCE UNLESS
OTHERWISE SPECIFIED:UP TO 5 ±0.2
ABOVE 5 ~ 30 ±0.3
ABOVE 30 ±0.5
ANGLE ±3°ANGLE
0°±3°APPROVAL
SCALE

2:1

DATE
PAGE31-03-2012
1 OF 1

F

E

D

C

B

A