



手柄位置及导通端子示意图

	POS. 1	POS. 2	POS. 3
Model NO.			
101	ON	NONE	OFF
SCHEMATIC		NONE	

**Technical characteristics**

SPECIFICATION: 3 A max. @ 125 VAC.  
 1.5 A max. @ 250 VAC.  
 MECHANICAL LIFE: 40,000 make-and-break cycles.  
 CONTACT RESISTANCE: 20mΩ max. initial @ 2-4VDC  
 100mA for both silver.  
 INSULATION RESISTANCE: 1000 MΩ min.  
 DIELECTRIC STRENGTH: 1000 VAC min.  
 OPERATING TEMPERATURE: -30°C to +85°C.

**Materials**

CASE: PPA (UL 94V-0)  
 HOUSING: Stainless Steel.  
 ACTUATOR: Alloy, chrome plated.  
 BUSHING: Alloy, nickel plated.  
 CONTACT/TERMINALS: Copper alloy silver plated.  
 RoHS

**东莞市溪榜电子有限公司**  
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

公差 TOLERANCES		.X± 0.4 .XX± 0.25		角度 ± 5°		UNIT 单位 mm	SCALE 1:1
版本 VERSION	A0	比例尺 SCALE	NONE	日期 DATE	2021.6.25	TITLE 图名	Sub-Miniature Toggle Switch
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY	WSL	DWG NO. 料号	
版本 VER.	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	APPROVED BY		PART NO. 型号	XB-ST-0-101-A01-T000-RS