



CIRCUIT DIAGRAM



PCB LAYOT

FEATURES

特征

Light operating force.

轻操作力。

Long term low contact resistance.

长期接触电阻低。

Momentary or latching operation.

固定或闭锁操作。

Short stroke 1.5mm to latch.

短行程1.5毫米至闭锁。

SPECIFICATIONS

1.ELECTRICAL

Contact rating	0.1A,30VDC
Contact resistance	50mVMax.
Insulation resistance	100MWMin. at 250VDC
Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

Temperature rating	Operating:-15℃ to+55℃ Storage: -25 ℃ to +65℃
Operation force	250±50gf
Stroke	Lock Stroke: 1.5+0.2mm Full Stroke: 2.0+0.2mm
Operating life	full load: 1x10 ⁴ cycles no load: 1 x10 ⁵ cycles
Contact form	DPDT

PAPT NO	XB5858-X-F-75
OPERATION	W:NO LOCK Z:LOCK

⑦	Contact	—	2	Phosphor bronze	Plating silvering	—
⑥	Terminal	—	6	Brass	Plating silvering	—
⑤	Spring	—	1	Sus	Natural	—
④	Base	—	1	Ppa		—
③	Crochet Needle	—	1	Sus	Natural	—
②	Cover	—	1	Ppa		—
①	Keystake	—	1	Ppa		—
ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK

				ANGLAR	±5°
				L ≤ 4	±0.2
				4 < L ≤ 16	±0.3
				16 < L ≤ 63	±0.4
				L > 63	±0.5
				UNSPECIFIED TOLERANCES	
	DATE	REVISED	APPROVED		

www.alpsr.com www.gdxjdz.com www.xbswitch.com



DSND		SCALE: N/A	MODEL TYPE:
DWN		VIEW:	KEY SWITCH
CHKD		UNIT: mm/in	PART NO.:
APPD		SIZE: A4	XB5858-X-F-75
			DWG NO.:

DONG GUAN XI BANG ELECTRONIC CO., LTD

WEIGHT	SHEET	REVISIC
	1/1	A0