






NOTE:
Rating: DC 12V 50mA
Operating Force: 200±100gf
Lifetime: 10,000 Cycles

PAPT NO	L
SS-3268S-L1	2.0
SS-3268S-L2	3.0
SS-3268S-L3	4.0
SS-3268S-L4	5.0

		—				—
		—				—
5	Terminal	—	12	Brass (0.30t)	ag Plated	—
4	Contact spring	—	1	Phosphor branze	ag Plated	—
3	Base	—	1	Lcp	Black	—
2	Cover	—	1	Sus	Natural	—
1	Keystake	—	1	Pa46	Black	—
ITEM	PAPT NAME	TER,NO	QTY	MATERIAL	FINISHING	REMARK

				ANGLAR	±5°
				L ≤ 4	±0.2
				4 < L ≤ 16	±0.3
				16 < L ≤ 63	±0.4
				L > 63	±0.5
				UNSPECIFIED TOLERANCES	
	DATE	REVISED	APPROVED		



DSND		SCALE: N/A	MODEL TYPE: SLIDE SWITCH
DWN		VIEW:	PART NO.: SS-3268S-X
CHKD		UNIT: mm/in	DWG NO.:
APPD		SIZE: A4	
		WEIGHT	SHEET
			1/1
		REVISI	A0