



SPECIFICATION:

- 1. RATING: DC 30V 0.5A;
- 2. CONTACT RESISTANCE: $\leq 30\text{M}\Omega$;
- 3. INSULATION RESISTANCE: $\geq 100\text{M}\Omega$ (DC 250V);
- 4. WITHSTAND VOLTAGE: 500VAC;
- 5. INSERTION AND EXTRACTION FORCE: 3-25N;
- 6. LIFE TEST: 5,000 CYCLES

	MATERIAL	PLATING
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
terminal 4	Brass	tin
plastic	Pbt	

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGULAR $\pm 5^\circ$
				$L \leq 4$ ± 0.2
				$4 < L \leq 16$ ± 0.3
				$16 < L \leq 63$ ± 0.4
				$L > 63$ ± 0.5

www.alpsr.com www.gdxjdz.com www.xbswitch.com



DONG GUAN XI BANG ELECTRONIC CO., LTD

DSND	SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK
DWN	VIEW:	PART NO.: PJ-319
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
	WEIGHT	SHEET
		1/1
	REVISION	A0