









P.C.B Layout



NOTES:

- 1.RATING: 12VDC 50mA
- 2.CONTACT RESISTANCE: 100mΩ Max
- 3.INSULATION RESISTANCE: 100MΩ 250VDC FOR 1MIN
- 4.DIELECTRIC STRENGTH: 250VAC(50/60Hz) FOR1MIN
- 5.LIFE TEST:100,000 CYCLES
- 6.OPERATION FORCE&TRAVEL: SEE SPECIFICATION

6	LED	BRONZE PLATED SILVER
5	COVER	PC/PET
4	PUSH BUTTON	PA66
3	SPRING PLATE	PBS SILVER CLAD
2	CASE	PA66
1	TERMINAL	SILVER PLATED BRONZE
NO.	PART NAME	MATERIAL



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

LED COLOR						
1	2	3	4	12	13	14
Red	Yellow	Green	Blue	Red Yellow	Red Green	Red Blue

TOLERANCE UNLESS OTHERWISE STATED				PART NO.: 带灯开关	TITLE TACT SWITCH
X.X	±0.25	mm	±0.5'	DRAWN DATE 2012.05.16	MODEL XB-TS-LED-HF02-108LM-XX
X.XX	±0.1	UNIT	mm	CHK'D DATE 2012.05.16	MATL
REV	A	SCALE	4:1		FINISH
SIZE	A4	SHEET	1 OF 1		

