









SCHEMATIC



PCB. 焊接图

主要技术规格:

- 1. 额 定 值: 50mA DC12V
- 2. 接触电阻: ≤100mΩ
- 3. 操 作 力: 160±30gf
- 4. 行 程: 0.3±0.1mm
- 5. 绝缘电阻: ≥100MΩ
- 6. 抗电强度: 250V 50HZ 1Min.
- 7. 寿 命: 500,000 Cycles

8					TOLERANCE UNLESS SPECIFIED				
7									
6									
5					WITHIN 1.5mm : ±0.1mm OVER 1.5mm : ±0.2mm	A ISSUE	2012-9-25 DATE	初 版 DESCRIPTIONS OF REVISION	ZENQ. CHEN APPD.
4	CONTACT	SUS	1	Ag CLAD	TITLE : TACT SWITCH			UNIT : mm	DRWG NO.: XB-TS-1161D-X
3	CASE	PPA/BRASS SRTIP	1	BLACK/Ag PLATED	MODEL:			SCALE: 5:1	DWN. JUN. YANG 2012-9-25
2	COVER	STEEL STRIP	1	Ni PLATED				CHK'D	DONG. PANG 2012-9-25
1	KNOB	PPA	1	BLACK				APPD.	ZENQ. CHEN 2012-9-25
NO.	PARTS	MATERIALS	Q'TY	FINISH	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONI CS CO., LTD.				