




INKJET CODE Description : XX X XX XX

XX-YEAR: 20 = 2020


X-MONTH: A = JAN, B = FEB,.....

XX-DAY: 14 = 14th DAY

XX-HOUR: 14 = 14 PM



INKJET CODE



#### Specifications

Current Rating 14 AWG: 13.0Amp AC/DC  
16 AWG: 13.0Amp AC/DC  
18 AWG: 10.0Amp AC/DC  
20 AWG: 7.5Amp AC/DC

Voltage Rating: 250V AC/DC.

Insulation Resistance:1000MΩMin.

Dielectric Withstanding Voltage:1500VAC

Contact Resistance:20mΩMax.

Operating Temperature:-55°C to +125°C

Materials

Insulator Material:High Temperature

Thermoplastic, UL 94V-0 PA66

or the equivalent material



★ All materials must meet Greenconn hazardous substances control standards.

★: Critical Characteristics.

indicates product characteristics, functionalities, and manufacturing processes regarding to customer's specifications

★: Safety Features

indicates product characteristics, functionalities, and manufacturing processes complying to legal regulations stated by local government



东莞市溪榜电子有限公司

DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV. A UNIT. mm SCALE. 3:2

3RD.ANG  
PROJ.



PAGE. 1/1

#### GENERAL TOLERANCE

X'±3.0"	X.±0.30
.X'±2.0"	.X±0.25
.XX'±1.0"	.XX±0.20
.XXX'±0.5"	.XXX±0.15

DESIGNED:

DATE:

CHECKED:

DATE:

APPROVED:

DATE:

DWG. NO.

XB-AGZ081-02APA

PART NO.

XB-AGZ081-02APA

TITLE.

2 WAY PLUG  
STANDARD SEAL  
DT SERIES