



ROHS



1. Rating : DC 30V 10A;
2. Contact resistance: $\leq 30\text{m}\Omega$;
3. Insulation resistance: $\geq 100\text{M}\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 5-20N;
6. life test: 10,000 cycles.

8				TOLERANCE UNLESS SPECIFIED				
7								
6				WITHIN 1.5mm : ±0.1mm	A	2012-9-25	初版	
5				OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION APPD.	
4	CONTACT	SUS	1	Ag CLAD	TITLE : DC Power Jack		UNIT : mm	DRWG NO.: XB-DC-135
3	CASE	PPA/BRASS SRTIP	1	BLACK/Ag PLATED	MODEL: XB-DC-135		SCALE: 5:1	DWN. JUN. YANG 2012-9-25
2	COVER	STEEL STRIP	1	Ni PLATED	东莞市溪榜电子有限公司		CHK'D DONG. PANG	2012-9-25
1	KNOB	PPA	1	BLACK	DONG GUAN XI BANG ELECTRONICS CO., LTD.		APPD. ZENQ. CHEN	2012-9-25
NO.	PARTS	MATERIALS	Q'TY	FINISH				