




REV	ECN No.	DESCRIPTION	DESIGN	DATE
A0		Release	吴丹平	2015.07.23





主要技术参数 Main Specifications


线 数 (Poles): 04 to 12
 接触电阻 (Contact resistance): $\leq 20\text{m}\Omega$
 绝缘电阻 (Insulation resistance): $\geq 1000\text{M}\Omega$
 额定电压 (Rated voltage): 125V AC DC
 额定电流 (Rated current): 1.0A AC DC
 耐 电 压 (Withstand Voltage): 1000V AC/minute
 温度范围 (Temperature Range): $-40^{\circ}\text{C} \sim +110^{\circ}\text{C}$

ORDER INFORMATION:

XB-L041A-***-B1MA-P			
PART No.			
No. FOR CIRCUITS:			PACKAGING:
202~206			P=PE
PLASTIC MATERIAL:			PLATING:



Assembly Layout



SUGGESTED PCB LAYOUT
(COMPONENT SIDE)

Circuit	Dimensions (mm)	
	DIM. A	DIM. B
L041A-2X2	5.00	2.50
L041A-2X3	7.50	5.00
L041A-2X4	10.00	7.50
L041A-2X5	12.50	10.00
L041A-2X6	15.00	12.50

C				
B	CONTACT	4~12PCS	Brass	Sn-plated
A	HOUSING	1 PCS	PA46	UL 94V-0, COLOR:BEIGE
ITEM	COMPONENT	Q'TY	MATERIAL	FINISH
 东莞市溪榜电子有限公司 Switch Connector DONG GUAN XI BANG ELECTRONICS CO., LTD				
X.±0.5	X.±5°	USE: CUSTOMER		PART NO.:
.X±0.3	.X±2°	APPD: 邵敬和		L041A-***-B1MA-P
.XX±0.25	.XX±1°	CHKD: 田 峰		DWG NO.:
--	--	DR: 吴丹平		GCCP-0474
UNITS: mm		SCALE 1 : 1		SHEET 1 / 1