



CAD FILE:

Waterproof IP67

ROHS



2. 认证:




0.1A 125/250VAC
0.1A 48VDC
3A 12VDC
40T130 μ 1E5



0.1A 250VAC
0.1A 48VDC
3A 36VDC
40T130 μ 5E4

3. 电路简图



1. 技术参数(Technical Parameters)

序号	主要技术参数(Main Technical Parameters)
1	电气额定值(Electrical Rating): 0.1A 125/250VAC; 3A/12VDC
2	环境温度(Ambient temperature): 40T130
3	电气寿命(Electrical lifetime): 5E4 cycles
4	操作力(Operating force): 3.0N MAX
5	自由位置(OP): 7.7±0.3mm (推动子上测)
6	动作位置(OP): 7.2±0.5mm (推动子上测)
7	接触电阻(Contact Resistance): ≤50mΩ (不带线)
8	耐压(Withstand Voltage): 脚与脚500V/60S/5mA, 脚与壳1500V/60S/5mA
9	绝缘电阻(Insulation Resistance): ≥100MΩ (Test Voltage 500VDC)
10	防护等级: IP67

8					TOLERANCE					
7					UNLESS SPECIFIED					
6					WITHIN 1.5mm : ±0.1mm	A	2012-9-25	初 版		ZENQ. CHEN
5					OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION		APPD.
4	CONTACT	SUS	1	Ag CLAD	TITLE : XB Micro Switch			UNIT : mm	DRWG NO.: XB-FSK-20-D242	
3	CASE	PPA/BRASS SRTIP	1	BLACK/Ag PLATED	MODEL: XB-FSK-20-D242			SCALE: 5:1	DWN.	JUN. YANG
2	COVER	STEEL STRIP	1	Ni PLATED						2012-9-25
1	KNOB	PPA	1	BLACK					CHK'D	DONG. PANG
										2012-9-25
NO.	PARTS	MATERIALS	Q'TY	FINISH					APPD.	ZENQ. CHEN
										2012-9-25