



RECOMMENDED PCB LAYOUT
T=1.2MM,TOLERANCES $\pm$ 0.05MM

NOTE:

1. MATERIAL:

1.1 HOUSING: PA9T, UL 94V-0

1.2 TERMINAL: C2680

2. FINISH:

2.1 TERMINAL: NICKEL 50 μ MIN UNDER PLATED
OVERALL, Au PLATED ON THE CONTACT AREA.
OR Tin ON THE SOLDERING AREA.

3. PRODUCT SPECIFICATION

3.1 CURRENT RATING :5A

3.2 VOLTAGE RATING : 30V AC

3.3 DIELECTRIC WITHSTANDING VOLTAGE:500VAC

3.4 INSULATION RESISTANCE: 100M Ω min.

3.5 CONTACT RESISTANCE: 30m Ω Max.

3.6 Operating Temperature: -40° ~105°

XG 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. $\pm$ 0.5 X.x $\pm$ 0.35 X.xx $\pm$ 0.25 ANGULAR $\pm$ 2 $^{\circ}$	DESIGN	PENG. GAO	DATE	TITLE: XB-B01M-R1-A-15P		
	APPROVED	FEO. LONG. HE	DATE			
	PART NO			REV: 01	SCALE: 1:1	UNIT: MM
	DRAWING NO			SIZE: A4	SHEET: 1/1	