








SCHEMATIC (NON-SHORTING)



SPECIFICATIONS

Rating	3A 250V AC;6A 125 AC
FUNCTION	2P-5T
Contact Resistance	50MΩ Max
Insulation Resistance	100MΩ Min
Operating Force	400gf±100gf
Operating Life	10,000cycle

Model No	X (mm)
XB-T26-K2522-12P-SMD-G2	2mm
XB-T26-K2522-12P-SMD-G3	3mm
XB-T26-K2522-12P-SMD-G4	4mm
XB-T26-K2522-12P-SMD-G5	5mm
XB-T26-K2522-12P-SMD-G6	6mm
XB-T26-K2522-12P-SMD-G7	7mm
XB-T26-K2522-12P-SMD-G8	8mm
XB-T26-K2522-12P-SMD-G9	9mm
XB-T26-K2522-12P-SMD-G10	10mm

7	STEEL BALL	STEEL	1	NATURAL
6	SPRING	STEEL WIRE	1	NATURAL
5	CONTACT	BRASS	1	Ag PLATED
4	TERMINAL	BRASS	12	Ag PLATED
3	CASE	PA66	1	BLACK
2	COVER	PA66	1	BALCK
1	KNOB	PA66	1	BALCK
NO	PARTS	MATERIALS	Q' TY	FINISH

6	新增Rating选项		
5	更新样式		
4	更新Rating		
3	更新Rating		
2	新增SPC		
1	更新版面		
ITEM NO.	DESCRIPTION	DRAWN	DATE

XB 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 - 30 ±0.3
Above 30 - 50 ±0.4
Angle ±0.5
3RD. ANGEL'S

DRAWN BY:	DATE	MAT'L	TI' TLE
PENG GAO	01/29/24	FINISH	MODLE
CHECKED BY:	DATE	SCALE	DWG NO.
ZENG CHEN	01/29/24	1:1	XB-T26-K2522-12P-SMD
APPROVED BY:	DATE	SHEET NO.	PART NO.
ZENG CHEN	01/29/24	1 of 1	XB-T26-K2522-12P-SMD
			SIZE
			A4
			VER