




ROHS



CUT-OUT



Switch Specifications

Rating: 6A 250VAC ;

2A 36VDC ;

Degree of protection: IP67;

Contact Resistance: 50mΩ Max. ;

Dielectric Strength: 2000VAC For 1 minute ;

Total Travel: 1.5 ± 0.5mm ;




Operating Force: 450 ± 150gf ;

Mechanical Life: 200,000 cycles ;

Load Life: 50,000 cycles ;

Operating Temperature: -20° C ~ 85° C ;

Function: OFF-(ON)



Panel Thickness: 6mm MAX.

MATERIAL:

Actuator: SUS ;

Top Base: SUS;

Bottom Base: PA66+GF ;

Terminal: Brass, Silver plated ;

Nut: Brass, Ni plated .


The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD

TITLE : METAL PUHS BUTTON SWITCH

MODEL : XB-PBM16-11M-H-NNN-SO



TOLERANCE
≤ 1.5mm ± 0.1
> 1.5mm ± 0.2
> 10mm ± 0.3

ANGLE
± 2°

7	SPRING	STEEL WIRE	1	NATURE
6	STEEL BALL	STEEL	1	NATURE
5	BOARD	PHENOLIC RESIN	1	NATURE
4	CONTACT CLIP	PBS STRIP	2	Ag PLATED
3	FRAME	IRON STRIP	1	Ni PLATED
2	TERMINAL	BRASS STRIP	8	Ag PLATED
1	KNOB	POM	1	BLACK
NO.	PART NAME	MATERIAL	QTY.	FINISHING

UNIT : MM	DWN.	ZENQ. CHEN	DATE	
SCALE : 3 : 1	CHK'D	PENG. GAO	DATE	
VERSION	01	APPD.	FEI. LONG. HE	DATE