

SWITCHING CIRCUIT



W6	白色	5.0	6.0	9.0	15
U6	蓝色	5.0	6.0	9.0	15
G6	纯绿色	5.0	6.0	9.0	15
Y6	黄色	5.0	6.0	9.0	15
R6	红色	5.0	6.0	9.0	15
W3	白色	2.8	3.0	3.4	15
U3	蓝色	2.8	3.0	3.4	15
G3	纯绿色	2.8	3.0	3.4	15
Y2	黄色	1.8	2.0	2.4	15
R2	红色	1.8	2.0	2.4	15
灯发光颜色 X Emitted color X	最小 一般 最大 额定电压(V)				额定 电流 (mA)

MATERIAL:

Actuator: SUS ;
Top Base: SUS;
Bottom Base:PA66+GF ;
Terminal: Brass,Silver plated ;
Nut: Brass. Ni plated .

装配步骤:

1. 将固定部件装配到面板上, 用螺母进行固定。
2. 将功能部件卡扣与固定部件凹槽对应后进行装配。
3. 装配后产品总高度如图示。


The material contained in this drawing is the property of XiBang. Any use other than that specifically authorized by XiBang is prohibited. The above drawing IS subjected to change for improvement without prior notice.



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO.,LTD

TITLE : METAL PUHS BUTTON SWITCH

MODEL : XB-PS30-22Z-F-RR2-S0



TOLERANCE
 $\leq 1.5\text{mm} \pm 0.1$
 $> 1.5\text{mm} \pm 0.2$
 $> 10\text{mm} \pm 0.3$

ANGLE
 $\pm 2^\circ$

额定电流		约15mA	约3mA	灯发光颜色 X	最小	一般	最大	额定 电流 (mA)
降压方式		采用3V灯, 需内置电阻		Emitted color X	顺向电压(V)			
7	SPRING	STEEL WIRE		1	NATURE			
6	STEEL BALL	STEEL		1	NATURE			
5	BOARD	PHENOLIC RESIN		1	NATURE			
4	CONTACT CLIP	PBS STRIP		2	Ag PLATED			
3	FRAME	IRON STRIP		1	Ni PLATED			
2	TERMINAL	BRASS STRIP		8	Ag PLATED			
1	KNOB	POM		1	BLACK			
NO.	PART NAME	MATERIAL		QTY.	FINISHING			