


REV.	ZONE	DESCRIPTION	DESIGN	DATE
A		NEW		



RECOMMENDED PCB LAYOUT (t=0.80±0.05)
COMPONENT SIDE (GENERAL TOLERANCE: ±0.05)

NOTES:

1.MECHANICAL:

MATING FORCE: 5-20N .
UNMATING FORCE: 8-20N .
DURABILITY: 10000 CYCLES MIN.

2.ELECTRICAL:

CURRENT: 5.0A MAX
VOLTAGE: 20V MAX
WITHSTANDING VOLTAGE: 100V AC
CONTACT RESISTANCE: 40 mΩ MAX INITIAL;
50 mΩ MAX AFTER 10000 CYCLES

3.ENVIRONMENTAL

OPERATING TEMPERATURE RANGE -30°C ~ +80°C

表1

品名	规格
1030024	LCP黑
1030025	LCP白
1030026	PA9T黑
1030027	PA9T白

④	GND LATCH	1	STAINLESS STEEL	NICKEL PLATED OVERALL, TAB WITH LEAD FREE TIN ALLOY.
③	CONTACT	16	COPPER ALLOY	NICKEL UNDERPLATING OVER ALL, GOLD PLATING AT - CONTACT AREA. LEAD FREE TIN ALLOY AT TERMINATION.
②	SHELL	1	STAINLESS STEEL	CLEAN.
①	HOUSING	2	THERMOPLASTIC UL 94V-0	MOLDED COLOR: BLACK. white
NO.	DESCRIPTION	QTY.	MATERIAL	TREATMENT

X.	±0.50	X.*	± 2°	UNITS mm
.X	±0.30	.X.*	± 1°	
.XX	±0.10	.XX.*	± 0.5°	
.XXX	±0.05			

THE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DONGGUAN XIBANG ELECTRONICS CO., LTD AND SHALL NOT BE REPRODUCED OR USED WITHOUT THE WRITTEN CONSENT OF DONGGUAN XIBANG ELECTRONICS CO., LTD	FINISH	APPD:	DWG NO: 参考表1
	Q'TY	CHKD:	
		DR:	

东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.			
TYPE-C 16PIN立式贴片公头 高H=11.94MM			
SCALE SHEET REV. 1/1 1/1 A			

USB TYPE C 接线示意图	
A4、A9、B9、B4	V
A5	
B5	
A1、A12、B1、B12	G
A6	D+
A7	D-
(R1=56KΩ R3=56KΩ) 5%	