


Specifications

Current Rating : 2.0 Ampere
 Insulation Resistance : 1000 MΩ Min
 Dielectric Withstanding : 500V AC
 Contact Resistance : 20 mΩ Max
 Operating Temperature : -40°C to +105°C




Materials

Contact Material : Brass
 Insulation Material : High Temperature Thermoplastic, 94V-0 Nylon

All materials must meet Greenconn's requirements for environmental protection.



Mating with



* For Coded Dimension Not Inside The Table, Please Refer To "Ordering Information"

No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information			No. of Pins/Row	Dimension Information		
	C	D			C	D			C	D			C	D	
03	4.00	6.20		11	20.00	22.20		21	40.00	42.20		31	60.00	62.20	
04	6.00	8.20		12	22.00	24.20		22	42.00	44.20		32	62.00	64.20	
05	8.00	10.20		13	24.00	26.20		23	44.00	46.20		33	64.00	66.20	
06	10.00	12.20		14	26.00	28.20		24	46.00	48.20		34	66.00	68.20	
07	12.00	14.20		15	28.00	30.20		25	48.00	50.20		35	68.00	70.20	
08	14.00	16.20		16	30.00	32.20		26	50.00	52.20		36	70.00	72.20	
09	16.00	18.20		17	32.00	34.20		27	52.00	54.20		37	72.00	74.20	
10	18.00	20.20		18	34.00	36.20		28	54.00	56.20		38	74.00	76.20	
				19	36.00	38.20		29	56.00	58.20		39	76.00	78.20	
				20	38.00	40.20		30	58.00	60.20		40	78.00	80.20	



东莞市溪榜电子有限公司
 DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV. 01 UNIT. mm SCALE. 5:1 PAGE. 1/1

GENERAL TOLERANCE

X' ± 5.0'	X ± 0.30
.X' ± 3.0'	.X ± 0.25
.XX' ± 2.0'	.XX ± 0.15
.XXX' ± 1.0'	.XXX ± 0.10

DESIGN:

CHECKED:

AUDITED:

APPROVED:

DATE:

DATE:

DATE:

DATE:

DWG. NO.

XB-PZ-C-20-217

PART NO.

XB-PZ-C-20-217

TITLE:

2.00 FEMALE HEADER
 SINGLE ROW DIP TYPE
 BASE 4.30H