










SECTION A-A




RECOMMENDED PCB LAYOUT
TOP VIEW TOLERANCE: ± 0.05



MATING PLUG
XB-DP550250-0188

SPECIFICATION:

1. RATING: DC 20V 20A
2. CONTACT RESISTANCE:
30m Ω MAX.(INITIAL)
50m Ω MAX.(FINAL)
3. INSULATION RESISTANCE: 100 M Ω MIN.
4. WITHSTAND VOLTAGE: 500 VAC
5. INSERTION FORCE: 3N~30N
6. EXTRACTION FORCE: 3N~30N
7. DURABILITY: 5,000 CYCLES



D	GROUND	SUS 304		1
C	SHELL	COPPER ALLOY	Ni 40u"MIN.	1
B	CENTER PIN	BRASS	GOLD FLASH/Ni 40u" MIN.	1
A	HOUSING	HIGH TEMP.THERMOPLASTIC	BLACK	1
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY



UNLESS OTHERWISE
SPECIFIED TOLERANCES

XG 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

DECIMALS:		ANGLES:		DESIGN:	GAO. PENG	PART NAME:	
DIM	TOL	DIM	TOL	CHECK:	2023.12.18	Φ5.5 立式(H=12.1)	
X.	±0.50	X.	±2°		DC POWER JACK		
X.X	±0.30	X.X	±1°		PART NO.		
X.XX	±0.20	X.XX	——			XB-DC-550250-1566	
X.XXX	±0.10	X.XXX	——				
		UNIT: mm		APPROVED	HE. LONG. FEI	SHEET: 1/2 REV.: A1	
					2023.12.18	DRAWING NO	


REV.	ECN NO.	DESCRIPTION	DESIGN	DATE
------	---------	-------------	--------	------

拉出方向



备注:

- 材料规格:
 - 载带:T=0.50mm
 - 包装盘:蓝色
 - 纸箱: L=385,W=385,H=380
- 包装数量:
250PCS/卷, 10卷(2500PCS)/箱
- 上盖带剥离力: 0.1N~0.7N(10~70gf);
剥离角度: 165°~180°;
剥离速度: 300mm/分钟.



包装盘标签

总共10层

PE袋:

外箱, 1PCS

透明胶带

INSIDE DIM.

INSIDE DIM.

INSIDE DIM.

UNLESS OTHERWISE
SPECIFIED TOLERANCES



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

DECIMALS: ANGLES:

DIM	TOL	DIM	TOL
X.	±0.50	X.	±2°
X.X	±0.30	X.X	±1°
X.XX	±0.20	X.XX	±1'
X.XXX	±0.10	X.XXX	±1''

3RD ANGLE PROJECTION

DESIGN: GAO. PENG
2023.12.15

CHECK:

APPROVED HE. LONG. FEI
2023.12.15

PART NAME:
DC POWER JACK
包装图

PART NO.
XB-DC-550250-1566

SHEET: 1/1 REV.: A1
DRAWING NO

REV.	ECN NO.	DESCRIPTION	DESIGN	DATE
------	---------	-------------	--------	------