


ROHS



SPECIFICATION


- 1.Rating : DC 30V 0.5A ; 1.0A ;
- 2.Contact resistance : $\leq 30\text{m}\Omega$;
- 3.Insulation resistance : $\geq 100\text{M}\Omega$;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-20N
- 6.life test : 5,000 cycles °

2	BRASS	NICKEL
1	POM	BLACK
NO	MATERIAL	DISPOSE



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO.,LTD

TITLE :	XB Audio Plug		
MODEL :	XB-P2503-L33	2.5	3节



UNIT : MM		DWN.	ZENQ. CHEN	DATE	TOLERANCE ≤1.5mm ± 0.1 > 1.5mm ± 0.2 ≥10.0mm ± 0.3	ANGLE TOL ± 2°						
SCALE : 3 : 1		CHK'D	DONG. PANG	DATE			2	TERMINAL	PBS STRIP	5	Ag PLATED	
VERSION		01	APPD.	FEI. LONG. HE			DATE	1	HOUSING	PBT	1	BLACK
								NO.	PART NAME	MATERIAL	QTY.	FINISHING