



NOTE

1.Material

Plunger: Brass

Barrel: Brass

Spring: SUS

Housing: PA46

2.Plating

Plunger: Au over NI

Barrel: Au over NI

3.Electrical

Rated current & voltage: DC 12V; 2.0A Max.

4.Mechanical

Spring force: 60g±20% at normal working height

Durability: 10,000 cycles(minimum)

5.To ensure the best usage,please operateit based on the working height Based on the engineering drawings,shall not exceed the maximum allowed compression

6.To avoid arcing issue, The adaptor startto power supply after connector mated fully.

塑胶: 9P-2.3PH-9.6H (SQ41母座)

吸塑: XYX-02 SQ41吸塑*0.45厚 (实际60PCS)

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.TOLERANCE UNLESS
OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°3RD.
ANGEL'S

UNITS

MM

DRAWN BY:
Jack LuDATE
04/01/21CHECKED BY:
Jacky ChenDATE
04/01/21APPROVED BY:
Tony KaoDATE
04/01/21

MAT'L

FINISH

SCALE

SHEET NO.

TITLE

MODLE

DWG NO.

PART NO.

CONNECTOR

POGO PIN

XB-PGC-X-250-9PX-M

Thimble Connector

SIZE
A4
VER
R