







Specifications
Current Rating:2.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:500VAC
Contact Resistance:20mΩMax.
Operating Temperature:-40°C to +105°C
Materials
Contact Material:
Brass(Pin length less than 25mm)
Phosphor Bronze(The total length of pin is more than 25mm)
Insulator Material:
PBT(Not resistant to high temperature),
Nylon(High temperature resistance),
LCP(High temperature resistance),
UL 94V-0
All materials must meet XI BANG hazardous substances control standards.

Recommended P.C.Board Layout
(Tolerance:±0.05)



No. of PIN/ROW	Dimension Information	
	M	L
03	4.00	6.00
04	6.00	8.00
05	8.00	10.00
06	10.00	12.00
07	12.00	14.00
08	14.00	16.00
09	16.00	18.00
10	18.00	20.00
11	20.00	22.00
12	22.00	24.00
13	24.00	26.00
14	26.00	28.00
15	28.00	30.00
16	30.00	32.00
17	32.00	34.00
18	34.00	36.00
19	36.00	38.00
20	38.00	40.00
21	40.00	42.00
22	42.00	44.00
23	44.00	46.00
24	46.00	48.00
25	48.00	50.00
26	50.00	52.00
27	52.00	54.00
28	54.00	56.00
29	56.00	58.00
30	58.00	60.00
31	60.00	62.00
32	62.00	64.00
33	64.00	66.00
34	66.00	68.00
35	68.00	70.00
36	70.00	72.00
37	72.00	74.00
38	74.00	76.00
39	76.00	78.00
40	78.00	80.00

Ordering Information

402 - XX XX A XXX C
Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple
Water code
Positioning column information
A=No locating post
B=Round post
C=Square post
Pin length
See the drawing
Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin
Insulator Material
A=PBT
R=Nylon(Halogen Free)
C=LCP
Color
1=Black
2=White
3=Yellow
E=Beige
Contact Material
A/S/K/T=Phosphor Bronze
B/Z/H/W=Brass
Packing code
A=Box
B=Tray
C=Tube
D=Tape&Reel
E=Cap+Tube
F=Cap+Tape&Reel
G=Acetate Tape+Tube
H=Acetate Tape+Tape&Reel

东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.
Switch Connector

GENERAL TOLERANCE	
X.*±5.0°	X.±0.30
.X.*±3.0°	.X.±0.25
.XX.*±2.0°	.XX±0.15
.XXX.*±1.0°	.XXX±0.10

DWG. NO.
XB-PZ-A-20-402
PART NO.

TITLE.
2.00 PIN
HEADER FOUR
ROWS DIP TYPE

REV.	UNIT.	SCALE.	PAGE.	
01	mm	4:1	1/1	