

F

E





D

C


B

A

123456789



Specifications
Current Rating:2.0Amp
Insulation Resistance:1000MΩMin.
Dielectric Withstanding Voltage:500VAC
Contact Resistance:20mΩMax.
Operating Temperature:-40°C to +105°C
Materials
Contact Material:
Brass(Pin length less than 25mm)
Phosphor Bronze(The total length of pin is more than 25mm)
Insulator Material:
Nylon(High temperature resistance),
LCP(High temperature resistance),
UL 94V-0
All materials must meet XI BANG hazardous substances control standards.



No. of PIN/ROW	Dimension Information		
	M	L	N
02	2.00	4.20	2.00
03	4.00	6.20	
04	6.00	8.20	4.00
05	8.00	10.20	6.00
06	10.00	12.20	8.00
07	12.00	14.20	10.00
08	14.00	16.20	12.00
09	16.00	18.20	14.00
10	18.00	20.20	16.00
11	20.00	22.20	18.00
12	22.00	24.20	20.00
13	24.00	26.20	22.00
14	26.00	28.20	24.00
15	28.00	30.20	26.00
16	30.00	32.20	28.00
17	32.00	34.20	30.00
18	34.00	36.20	32.00
19	36.00	38.20	34.00
20	38.00	40.20	36.00
21	40.00	42.20	38.00
22	42.00	44.20	40.00
23	44.00	46.20	42.00
24	46.00	48.20	44.00
25	48.00	50.20	46.00
26	50.00	52.20	48.00
27	52.00	54.20	50.00
28	54.00	56.20	52.00
29	56.00	58.20	54.00
30	58.00	60.20	56.00
31	60.00	62.20	58.00
32	62.00	64.20	60.00
33	64.00	66.20	62.00
34	66.00	68.20	64.00
35	68.00	70.20	66.00
36	70.00	72.20	68.00
37	72.00	74.20	70.00
38	74.00	76.20	72.00
39	76.00	78.20	74.00
40	78.00	80.20	76.00

Ordering Information

Plastic specifications
1=Single row
2=Dual row
3=Tripe row
4=Quadruple

Water code
201

Positioning column information
A=No locating post
B=Round post
C=Square post

Pin length
See the drawing

Insulator Material
R=Nylon(Halogen Free)
C=LCP

Color
1=Black
2=White
3=Yellow
E=Beige

Contact Material
A/S/K/T=Phosphor Bronze
B/Z/H/W=Brass

Packing code
A=Box
B=Tray
C=Tube
D=Tape&Reel
E=Cap+Tube
F=Cap+Tape&Reel
G=Acetate Tape+Tube
H=Acetate Tape+Tape&Reel

Plating code
01=Tin
02=Gold Flash
05=Gold Flash/Tin
22=Matte Tin



东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD.

REV.	UNIT.	SCALE.	PAGE.
01	mm	2:1	1/1

GENERAL TOLERANCE	
X.°±5.0°	X.±0.30
.X°±3.0°	.X±0.25
.XX°±2.0°	.XX±0.15
.XXX°±1.0°	.XXX±0.10

DWG. NO.	XB-PZ-D-20-201
PART NO.	

TITLE.	2.00 PIN HEADER DUAL ROWS SMT TYPE CONNECTOR
--------	--

123456789

F

E

D

C

B

A