



Notes:

Insulator: Glass filled Polyester UL 94V-0

① Shell: Steel, Nickel plated as standard

Ordering Code

C3W3 P0000 100 000
 ① ② ③ ④

① Series No.

② Connector Type:
 P0000= Plug

③ Insulator Color:
 100= Black
 600= Green

④ Mounting Style:

000= With $\phi 3.05$ mm holes on shell

A00= Riveted #4-40 UNC close nuts on front shell

B00= Riveted #4-40 UNC open nuts on front shell

C00= Riveted #4-40 UNC open nuts on rear shell

Mounting Style

RoHS Compliant

Code	000	Code	A00	Code	B00	Code	C00
			DIM. L= 5.8mm		DIM. L= 4.0mm		DIM. L= 4.0mm

④					DATE	UNIT: mm / inch	TITLE: C3W3 MALE COMBO D-SUB CONNECTOR (SOLDER CUP TYPE)	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD
③				DRAWN BY: Karen	1/17-18'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②				ENGINEER: Sun	1/23-18'	.X ± 0.30/.012 X: ± 1'	FINISH:	
①	Karen	1/17-18'	ECNT117262/ECRT117074	CHECKED BY: Easley	1/25-18'	.XX ± 0.20/.008 X: ±	DRAWING NO. C3W301SC PART NO. C3W3P0000*00*00	
SYM	NAME	DATE	REVISIONS	APPROVED BY: Easley	1/25-18'	.XXX ± 0.10/.004 XX: ±	SCALE 2 / 1 SHEET 1 OF 1	