



- ① Series No.
- ② Connector Type: S= Receptacle
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: H= Right Angle Dip type
- ⑤ High power contact plating:
 - 2= Gold flash plated over Nickel
 - 3= 15 μ " Gold plated over Nickel
 - 4= 30 μ " Gold plated over Nickel
 - 5= 50 μ " Gold plated over Nickel
- ⑥ Singal contact plating:
 - 0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 20= 20A
- ⑨ Mounting Style:
 - 000= With ϕ 3.05mm holes on shell
 - B00= Riveted #4-40 UNC open nuts on front shell
 - C00= Riveted #4-40 UNC open nuts on rear shell
 - I00= Riveted #4-40 UNC ground tabs
with ϕ 3.2mm holes
 - I10= Riveted #4-40 UNC ground tabs
with board locks(standard)

4					DATE	UNIT: mm / inch		TITLE: C5W5 20A HIGH POWER FEMALE D-SUB CONNECTOR (RIGHT ANGLE BOARD MOUNT TYPE)	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.			
3				DRAWN BY: Karen	3/20-17'	TOLERANCE UNLESS OTHERWISE SPECIFIED						
2				ENGINEER: Sun	3/20-17'	.X ± 0.30/.012	X' ± .1'	FINISH:				
1	Karen	3/20-17'	ECNT117049/ECRT117003	CHECKED BY: Eisley	3/22-17'	.XX ± 0.20/.008	.X ±					
SYM	NAME	DATE	REVISIONS	APPROVED BY: Eisley	3/22-17'	.XXX ± 0.10/.004	.XX ±		DRAWING NO. C5W512SC	PART NO. C5W5SPH*0*20***		
									SCALE	2 / 1	SHEET	1 OF 1