





Ordering Code

C8W8	S	P	V	3	0	1	20	D00
①	②	③	④	⑤	⑥	⑦	⑧	⑨

- ① Series No.
- ② Connector Type: S= Receptacle
- ③ Contact type: P= High Power Contact
- ④ Contact tail style: V= Straight Dip type
- ⑤ High power contact plating:
 - 2= Gold flash plated over Nickel
 - 3= 15 μ " Gold plated over Nickel
 - 4= 30 μ " Gold plated over Nickel
 - 5= 50 μ " Gold plated over Nickel
- ⑥ Singal contact plating:
 - 0= Without singal contact
- ⑦ Insulator color: 1= Black, 6= Green
- ⑧ Performance: 20= 20A
- ⑨ Mounting Style:
 - 000= With $\phi 3.05\text{mm}$ holes on shell
 - B00= Riveted #4-40 UNC open nuts on front shell
 - C00= Riveted #4-40 UNC open nuts on rear shell
 - D00= Riveted #4-40 UNC ground stand-off on rear shell(standard)



Mounting Style				RoHS Compliant			
Code	000	Code	B00	Code	C00	Code	D00
		DIM. L = 4.0mm 		DIM. L = 4.0mm 		DIM. L = 7.0mm 	

4						DATE	UNIT: mm / inch		TITLE: C8W8 20A HIGH POWER FEMALE D-SUB CONNECTOR (TOP ENTRY BOARD MOUNT TYPE)	XB Switch Connector 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONICS CO., LTD.	
3				DRAWN BY:	Rita	10/18-01'	TOLERANCE UNLESS OTHERWISE SPECIFIED				
2				ENGINEER:	David	10/19-01'	.X ± 0.30/012	X.* ± 1'			
1				CHECKED BY:	David	10/19-01'	.XX ± 0.20/008	X.* ±			
SYM	NAME	DATE	REVISIONS	APPROVED BY:	Alex	10/19-01'	.XXX ± 0.10/004	.XX.* ±	MATERIAL:		
									FINISH:		
										DRAWING NO. C8W808SB	PART NO. C8W8SPV*0*20*00
										SCALE 2 / 1	SHEET 1 OF 1