



SUA-110M2-30x-S277

鍍層厚度:

Blank	: 1u"
2	: 15u"
3	: 30u"

Pin NUMBER	SIGNAL NAME
1	VBUS
2	D-
3	D+
4	GND
5	StdA_SSRX-
6	StdA_SSRX+
7	GND_DRAIN
8	StdA_SSTX-
9	StdA_SSTX+
Shell	Shield

- SPECIFICATIONS:**
- MATERIAL:**
 - HOUSING: LCP, UL 94V-0
 - CONTACT: PHOSPHOR BRONZE
 - SHELL: BRASS
 - PLATING:**
 - TERMINAL: PLATED GOLD IN MATING AREA ;
TIN PLATED ON SOLDER BALLS ;
NICKEL UNDER PLATED OVERALL
 - SHELL: NICKEL UNDER PLATED SURFACE LAYER
 - ELECTRICAL CHARACTERISTICS:**
 - CONTACT RESISTANCE: 30mΩ MAXIMUM
 - CONTACT CURRENT RATING: 1.5A
 - DIELECTRIC WITHSTANDING VOLTAGE: 500 V R.M.S.
 - INSULATION RESISTANCE: 1000 MΩ MIN
 - OPERATING TEMPERATURE: -40°C ~ 85°C
 - MECHANICAL CHARACTERISTICS:**
 - MATING FORCE: 3.57kg MAX
 - UNMATED FORCE: 1.02kg MIN
 - DURABILITY: 1500 CYCLES

ITEM NO.	DESCRIPTION	DRAWN	DATE
5	更新圖面	Jack	040722
4	新增尺寸	Jack	100518
3	更新DURABILITY	Jack	090618
2	新增尺寸	Jack	061917
1	更新樣式	Jack	091216

XBS 东莞市溪榜电子有限公司
DONG GUAN XI BANG ELECTRONICS CO., LTD
 Switch Connector

TOLERANCE UNLESS OTHERWISE STATED:

Up to 5	±0.2
Above 5 ~ 15	±0.3
Above 15 ~ 30	±0.4
Above 30 ~ 50	±0.5
Angle	±0.3°

3RD. ANGEL'S

UNITS: MM

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	04/07/22		MODLE	USB 3.0 AF SMT本體長=14.45mm, 魚叉腳=2.70mm
CHECKED BY:	DATE	FINISH	DWG NO.	SCALE
Jacky Chen	04/07/22		SUA-110M2-30x-S277	1 : 1
APPROVED BY:	DATE	SHEET NO.	PART NO.	SIZE
Tony Kao	04/07/22	1 of 1	SUA-110M2-30x-S277	A4
				VER R5