

性能:

额定电流: 1.0A

额定电压: 12V

耐电压: 500V





接触电阻: 30mΩ MAX

绝缘电阻: 500MΩ

工作温度: -40℃~+85℃


塑件(材质): LCP E130I

接触点(材质): 铜合金, 触点镀金3u"




RECOMMENDED PCB LAYOUT

TOP VIEW (.XX±0.05)



PART NO.	DIM A	DIM B
XB-BC-21-2P170	2.54	
XB-BC-21-3P170	3.81	1.27
XB-BC-21-4P170	5.08	2.54
XB-BC-21-5P170	6.35	3.81
XB-BC-21-6P170	7.62	5.08
XB-BC-21-7P170	8.89	6.35
XB-BC-21-8P170	10.16	7.62

版本REV.	更新标记REVISION	日期DATE	未注公差 TOLERANCE	 东莞市溪榜电子有限公司 DONG GUAN XI BANG ELECTRONIC CO., LTD.
			X. ±0.35	
			X. ±0.25	
绘制DRAWN	高鹏		X.XX ±0.15	品名ARTICLE:
设计DES'D	庞东		X.XXX ±0.05	弹片电池座连接器正压
审核CHK'D	贺龙飞		视图方法 PROJECTION	图号MODEL:
批准APPV'D	杨军			XB-BC-21系列塑高1.7mm A4
比例SCALE:			单位UNIT: mm	页码SHEET: 共1页 第1页